

## Description

### 3 Axis 3D Dimension Joystick CCTV Keyboard Controllers for PTZ Speed Dome Camera

1. Communication Mode: RS-485 for the connection with mainframe.
2. Baud rate of communication: 1200/2400/4800/9600/19200 BIT/Sec.
3. Distance of communication: 1500M (0.5MM twisted-pair).
4. The keyboard can control up to 128 Speed Domes or Decoders etc terminal devices. The address of the Speed Domes or Decoders can be set within the range of: 1~255.
5. Variable-speed operation can be applied to the built-in Pan/tilt of the Speed Dome through the keyboard.
6. Lens zooming, focus and iris can be manually controlled through the keyboard.
7. Preset positions can be set up and previewed in Speed Dome through the keyboard.



## WTX-1201

Model	WTX-1201
Communication connection mode	RS-485 bus mode for controlling units
In-built multi-protocol	Pelco-D, Pelco-P, Pelco-D1, Pelco-P1, New
Baud rate of communication	2400/4800/9600/19200 BIT/S
Max controllable Cameras	128 units PTZ cameras or Decoders etc terminal devices
Range of communication	1.5KM (4900ft) with twisted-pair
The range for camera address	1-255
Power supply	DC9V - 12V 500mA
Power adapter provided	AC110V or 220V(±10%) switch to DC9V 500mA
Temperature Operation	-10 to 60°C
Relative Humidity	≤90%RH
Dimension	202L× 168W× 48Hmm